

### Bơm vòng xoáy QB

Type 型号	Dimensions 外型尺寸mm														Weight重量 ( kg)		Packing SIZE 包装尺寸( mm)			Packing QTY 包装数量 20' CONT 20' 柜
	a	f	h	H1	H2	l	m	m1	n	n1	w	b	g	s	NW	GW	L	W	H	
QB60	42	265	154	63	80	20	98	80	120	100	63	22	8	7	5.7	6.1	285	145	175	3400
QB70	55	291	179	71	85	20	110	90	134	112	68	23	8	7	8.8	9.3	310	180	205	2200
QB70H	55	291	179	71	85	20	110	90	134	112	68	23	8	7	8.8	9.3	310	180	205	2200
QB80	55	291	179	71	85	20	110	90	134	112	68	23	8	7	9	9.7	310	180	205	2200
QB90	90	405	193	108	85	20	130	100	152	125	100	25	10	9	17.7	18.7	420	195	225	1320

### TECHNICAL DATA 技术参数

Type 型号	Input power 输入功率		Current 电流 (A)	Capacitor 电容器 ( $\mu$ F)	H.max 最高扬程 (m)	Q.max 最大流量 (l/min)	Size 进出口径 (inch)	S.head 最大吸程 (M)	Total head 总扬程 (m)	Capacity 流量 l/min								
	KW	HP								5	10	20	30	40	50	60		
QB60	0.37	0.5	1.5	8	36	35	1" X 1"	9	Total head 总扬程 (m)	32	26	16	6					
QB70	0.55	0.75	2.4	12	55	40	1" X 1"	9		48	40	28	14	1				
QB70H	0.75	1	3.7	16	68	42	1" X 1"	9		60	52	36	22	6	4			
QB80	1.1	1.5	4.6	20	78	53	1" X 1"	9		71	64	49	34	19	28	10		
Qb90	1.5	2	6.4	30	84	70	1.5" X 1.5"	9		80	73	62	51	40				