SMALL DIESEL GENERATOR SET TECHNICAL DATA

| Model | GF-CD15 | |
|-------------------------------------|--|----------------|
| | Prime output | Standby output |
| Generator power (KW) | 12 | 15 |
| Generator power (KVA) | 15 | 18.75 |
| Max.Engine power (KW) | 16.2 | |
| Engine Model | ZS1115 | |
| Manufacturer | CHANGCHAI (China) | |
| Engine characters | 1-cylinder, 4-stroke | |
| Cooling method | Water - cooled | |
| Speed method | Mechanical | |
| Starting method | 12V2 one way start | |
| Fuel system | Direct-injection | |
| Lubrication method | use force to spray | |
| Displacement (L) | 1.1945 | |
| Compression Ratio | 17:1 | |
| Rated RPM | 2200 | |
| Bore and Stroke (mm) | 115 x 115 | |
| 100% (Prime power)load (L/h) | 33.63 | |
| Alternator model | MINYUAN | |
| Manufacturer | STC-15 | |
| Opening switch | MCCB Air switch | |
| Rated voltage/frequency | 3-phase, 4-wire, 400V/230V, 50Hz, 0.8 (Lagging) | |
| Voltage Adjust range | > 5% | |
| Voltage Regulation | ≥ 95% - 105% | |
| Voltage Regulation, Steady State | > ±1% | |
| Exciter Type | Brushless, self-exciting | |
| Insulation Class/Protection Grade | Class H/IP23 | |
| Efect factor of telecom TIF/THE | TIF<50/THF<2% | |
| Random accessories | Battery, battery's cable, Ripple flex exhaust, exhaust siphon, | |
| | flange | |
| Open type - Overall size (mm) | 1350 x 750 x 950 | |
| Weight (kg) | 460 | |
| Soundproof type - Overall size (mm) | 1570 x 890 x 1010 | |
| Weight (kg) | 680 | |

Note: Specifications may change without notice