

汽油/柴油泵

Type 型号	MY20-G	MY30-G	MY20-GH
Suction, discharge port diameter 进出口径[mm(in)]	50(2")	80(3")	50(2")
Cont.head 扬程(m)	32	28	50
Max suction head 最大吸程(m)	8	8	8
Cont.capacity 流量(L/min)	700	1000	400
Engine modle 发动机型号	TE168F	TE168	TE168
Max.Output 最大功率(PS/rpm)	5.5/3600	5.5/3600	5.5/3600
Recommended Power Output 额定功率(PS/rpm)	4.8/3600	4.8/3600	4.8/3600
Start system 启动系统	Recoil or Electric 手拉或电启动		
Fule tank capacity 油箱容量(L)	3.6	3.6	3.6
Overall dimension 外形尺寸(MM)	462×392×386	510×392×462	475×390×460
Net weight 净重(KG)	28	30.5	28
20FT(PCS)	410	312	295

TECHNICAL DATA 技术参数(Diesel water pumps柴油泵)

Type 型号	MY20-D	MY30-D	MY20-DH
Suction, discharge port diameter[mm(in)]	50(2")	80(3")	50(2")
Cont.head(m)	28	26	50
Max suction head(m)	8	8	8
Cont.capacity(L/min)	700	1100	400
Engine modle 发动机型号	TD170F	TD178F	TD178F
Max.Output 最大功率(PS/rpm)	3.5/3600	5.5/3600	5.5/3600
Recommended Power Output(PS/rpm)	3/3600	5/3600	5/3600
Start system 启动系统	Recoil or Electric 手拉或电启动		
Fule tank capacity 油箱容量(L)	2.5	3.5	3.5
Overall dimension 外形尺寸(MM)	470×410×480	560×450×515	560×450×515
Net weight 净重(KG)	37	47	47
20FT(PCS)	185	180	140