

YS(AO2) three-phase asynchronous motor

Model	Out Put		Voltage (V)	Current (A)	Rotation speed(r/min)	Effect (%)	Power factor	Default torque	Continuous current(A)	Maximum torque
	HP	W								
YS6312	0.25	180	380	0.53	2800	69	0.75	2.3	3.5	2.3
YS6322	0.33	250	380	0.68	2800	72	0.78	2.3	4	2.3
YS7112	0.5	370	380	0.96	2800	73.5	0.8	2.3	6	2.3
YS7112	0.75	550	380	1.35	2800	75.5	0.82	2.3	8	2.3
YS8012	1	750	380	1.75	2800	76.5	0.85	2.2	10.5	2.3
YS8022	1.5	1100	380	2.55	2800	77	0.85	2.2	16	2.3
YS90S-2	2	1500	380	3.44	2800	78	0.85	2.2	24	2.3
YS90L-2	3	2200	380	4.83	2800	80.5	0.86	2	34	2.3
YS6314	0.18	120	380	0.48	1400	60	0.63	2.4	3	2.4
YS6324	0.25	180	380	0.65	1400	64	0.66	2.4	4	2.4
YS7114	0.33	250	380	0.83	1400	67	0.68	2.4	5	2.4
YS7124	0.5	370	380	1.12	1400	69.5	0.72	2.4	7	2.4
YS8014	0.75	550	380	1.65	1400	73.5	0.73	2.2	9.5	2.4
YS8024	1	750	380	2.01	1400	75.5	0.75	2.3	12	2.4
YS90S-4	1.5	1100	380	2.75	1400	78	0.78	2.3	19.5	2.4
YS90L-4	2	1500	380	3.65	1400	79	0.79	2.3	25.5	2.4