

Asynchronous electric motor with capacitive start, aluminum housing, 1 phase MC

Model	Out Put		Current (A)	Power factor	Effect (%)	Rotation speed(r/min)	Default torque	Continuous current(A)	Maximum torque
	kW	HP							
MC711-2	0.18	0.24	1.89	0.72	60	2750	3	6.5	1.8
MC712-2	0.25	0.33	2.4	0.74	64	2770	3	6.5	1.8
MC801-2	0.37	0.5	3.36	0.77	65	2800	2.8	6.5	1.8
MC802-2	0.55	0.75	4.65	0.79	68	2810	2.8	6.5	1.8
MC90S-2	0.75	1	6.09	0.8	70	2820	2.5	6.5	1.8
MC90L-2	1.1	1.5	8.68	0.8	72	2820	2.5	6.5	1.8
MC100L1-2	1.5	2	11.4	0.81	74	2830	2.5	7	1.8
MC100L2-2	2.2	3	16.5	0.81	75	2830	2.2	7	1.8
MC112M-2	3	4	21.9	0.82	76	2840	2.2	7	1.8
MC711-4	0.12	0.16	1.88	0.58	50	1350	3	6	1.8
MC712-4	0.18	0.24	2.49	0.62	53	1370	3	6	1.8
MC801-4	0.25	0.33	3.11	0.63	58	1400	2.8	6	1.8
MC802-4	0.37	0.5	4.24	0.64	62	1410	2.8	6	1.8
MC90S-4	0.55	0.75	5.49	0.69	66	1420	2.5	6	1.8
MC90L-4	0.75	1	6.87	0.73	68	1420	2.5	6	1.8
MC100L1-4	1.1	1.5	9.52	0.74	71	1430	2.5	6.5	1.8
MC100L2-4	1.5	2	12.5	0.75	73	1430	2.5	6.5	1.8
MC112M-4	2.2	3	17.8	0.76	74	1440	2.2	6.5	1.8