## **DIESEL GENERATOR SET TECHNICAL DATA**

| MINIVIAN CENERATOR SET MODEL        | GF-S12   |                |
|-------------------------------------|--|----------------|
| MINYUAN GENERATOR SET MODEL         | Prime output   | Standby output |
| Generator power (KW)                | 11   | 12             |
| Generator power (KVA)               | 14   | 15             |
| Max.Engine power (KW)               | 13.8   |                |
| Engine Model                        | 295AD  |                |
| Manufacturer                        | SHANGCHAI  |                |
| Cylinder Arrangement                | 2 in line  |                |
| Cooling System                      | Water-cooled, radiator 40 °C max, fans are driven by belt, with safety guard |                |
| Governor Type                       | Mechanical   |                |
| Starting System                     | 12V/24V one way start  |                |
| Engine Filter                       | Dry type air filter, fuel filter, oil filter                                 |                |
| Fuel System                         | A type fuel pump   |                |
| Displacement (L)                    | 1.63   |                |
| Compression Ratio                   | 16.5:1   |                |
| Rated RPM                           | 1500   |                |
| Bore and Stroke (mm)                | 95x115   |                |
| 100% (Prime power)load (L/h)        | 3.3  |                |
| Total Oil Capacity (L)              | 9.3  |                |
| Alternator model                    | TFW-12   |                |
| Manufacturer                        | MINYUAN  |                |
| Opening switch                      | MCCB Air switch  |                |
| Rated voltage/frequency             | 400/230V; 50Hz   |                |
| Voltage Adjust range                | < 5%   |                |
| Voltage Regulation                  | ≥ 95% - 105%   |                |
| Voltage Regulation, Steady State    | < ±1%  |                |
| Exciter Type                        | Brushless, self-exciting   |                |
| Insulation Class/Protection Grade   | Class H/IP23   |                |
| Efect factor of telecom TIF/THF     | TIF<50/THF<2%  |                |
| Connecting type                     | 3 phase and 4 wires  |                |
| Random accessories                  | Battery, battery's cable, Ripple flex exhaust, exhaust siphon, flange        |                |
| Open type - Overall size (mm)       | 1400x600x910   |                |
| Weight (kg)                         | 520  |                |
| Soundproof type - Overall size (mm) | 1650x750x1110  |                |
| Weight (kg)                         | 750  |                |

Note: Specifications may change without notice