DIESEL GENERATOR SET TECHNICAL DATA

Standby output 350 438 339/372 2V135AZLD SHANGCHAI 12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
339/372 2V135AZLD SHANGCHAI 12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
339/372 2V135AZLD SHANGCHAI 12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
2V135AZLD SHANGCHAI 12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
SHANGCHAI 12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
12 in line max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
max, fans are driven by belt, with safe guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
guard Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
Mechanical / one way start filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
filter, fuel filter, oil filter type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
type fuel pump 25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
25.5 16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
16.4:0 1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
1500 135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
135x150 64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
64.8 57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
57.4 TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
TFW-350 MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
MINYUAN CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
CCB Air switch 0/230V; 50Hz < 5% 95% - 105%
0/230V; 50Hz < 5% 95% - 105%
< 5% 95% - 105%
95% - 105%
< ±1%
less, self-exciting
Class H/IP23
-<50/THF<2%
ase and 4 wires
ole flex exhaust, exhaust siphon, flang
00x1420x1700
3980
00x1850x2120
4360